



dDLC Digital Diode Laser Controller



The MOGLabs Digital Diode Laser Controller is our next-generation controller for precision tunable lasers. It combines the ergonomic ease-of-use of our classic analogue DLC, with the flexibility and performance of a fully digital system.

It offers a combination of impressive performance and ease-of-use, using the front panel with high resolution display, or our comprehensive Windows app, or your own code using the simple text-based command language that MOGLabs is famous for.

The dDLC is designed for the ultimate applications in quantum computing, quantum sensing, time and frequency standards, gas sensing, and spectroscopy.

Features

- Intuitive fully-feature controls for standalone operation
- FFT spectrum analyser
- Oscilloscope functionality built-in
- Ultra-low noise current source
- Temperature controller
- Demodulator (lock-in amplifier)
- Feedback servos: locking is **included**
- Auto-lock and auto-relock (in development)
- Modulator driver (dual channel DDS)
- Sweep ramp generator
- TCP/IP, USB2
- LabVIEW, MATLAB and python drivers

Digital Diode Laser Controller

Specifications dDLC 1.0 (preliminary)

Current		B1150 single-channel driver
Output current	0 to 800mA $\pm 5\mu\text{A}$ setpoint (display $\pm 10\mu\text{A}$), control $\pm 8\text{nA}$	
Noise*	240pA/VHz @ 1 kHz, 250nA (rms) 1 Hz – 1 MHz	
Stability and accuracy	$\pm 0.2\text{ppm}/^\circ\text{C}$ and 0.1% from setpoint	
Compliance voltage	8 V at 400mA, 4 V at 800mA	
Current modulation	1. $\pm 25\text{mA}$ Direct analogue, Sweep 2. $\pm 1\text{mA}$ Direct analogue, Dither, Control DAC 1, Control DAC 2 3. $\pm 250\mu\text{A}$ Dither, Control DAC 2 DAC1, DAC2: 16 bits at 3.125MHz	
Current modulation bandwidth	Direct analogue mode: 1.2 MHz (-3dB) DAC control (fast): 3.2 MHz (28-bit depth)	
Temperature		B1180 single-channel TEC driver
Range	7.5 – 49.5°C $\pm 1\text{mK}$ resolution	
Stability	Better than $\pm 1\text{mK}/^\circ\text{C}$	
TEC power	$\pm 2\text{A}$, $\pm 12\text{V}$ (24W)	
Sensor	NTC 10k Ω	
Control	PID with variable sample rate, bandwidth 50 Hz	
Protection	PCB over temp, TEC over current, open/short circuit	
Piezo		B1190 dual-channel piezo driver
Piezo output	Two independent channels 0 – 150V, $\pm 10\text{mA}$ (charge and discharge)	
Piezo Sweep/Control DAC	Individual Sweep and Control DACs, 16 bits unipolar	
Resolution	Sweep: 2.5mV resolution at maximum range Control: variable gain from 240 μV to 16 μV per LSB	
Noise	80nV/VHz	
Sweep	Internal 0.1 Hz to 62.5 Hz; auxiliary inputs ChA, ChB; programmable	
Monitoring	Voltage and current measurement for each channel	
Protection	Leakage, PCB over temperature	

Frequency stabilisation**B1110 core**

Dither for AC locking	0 to 2.5 MHz ± 0.058 Hz (default 250kHz) Dither to diode current ($\pm 250\mu\text{A}$ or $\pm 1\text{mA}$) or external ($\pm 150\text{mA}$ or $\pm 4\text{ V}$)
Bandwidth	3.2 MHz (DAC control)
Phase	0 – 360°, 0.022° resolution
Error signal	32-bits signed, sampling at 6.25 MHz
Post demodulator filter	5 stage IIR and user adjustable response including bypass option
Servo Controls	Slow (piezo) and Fast (current) servo controllers with individual offset
Gain Controls	$\pm 18\text{dB}$ master plus $\pm 18\text{dB}$ on slow, fast channels
Slow Controller Inputs	1. Slow Error Signal (after offset and master gain) 2. Auxiliary A 3. Auxiliary B 4. Photodetector DC Input 5. Fast controller Output
Slow Controller Action	PI with 20 dB/dec gain with user-adjustable response
Fast Controller Input Selection	1. Fast Error Signal (after offset and master gain) 2. DC Block Output (AC coupled error signal)
Fast Controller Action	PI with 20 dB/dec gain with user-adjustable response

Signal input/output**B1120 rear panel**

Signal input/output	8 BNC connectors 1 MOGLabs DVI-D DL socket Option: Toptica DL Pro	4 analogue input 2 analogue output Trigger out Mod out
Analogue inputs (4)	Signal range $\pm 4.096\text{ V}$ (protected to $\pm 15\text{ V}$) <i>Photodetector</i> AC: 12.5 MHz > 150dB dynamic range DC: 1 MHz > 110dB dynamic range <i>Auxiliary A and B</i> : DC 1 MHz > 110dB dynamic range <i>Direct</i> : analogue input direct to diode current modulation	
Analogue outputs (2)	Monitor A and B, 16 user-selectable signals; output range $\pm 4\text{ V}$. Sampling up to 3.25 MHz @ 16 bits / BW 1 MHz Dither Voltage/Current Driver (user selectable): output $\pm 4.096\text{ V}$ $\pm 150\text{mA}$ BW 1 MHz	
Digital inputs	TTL compatible, 0 – 6.5 V tolerant and protected, active low <0.8 V: a) 3.5mm stereo jack (external Fast/Slow Lock inputs) b) 3.5mm stereo jack (External Laser1/Laser2 interlocks)	
Digital outputs	TTL compatible, 0 – 6.5 V tolerant and protected, active high >2.4 V: a) Trigger (sweep mid-point) b) 3.5mm stereo jack (Fast/Slow Lock outputs)	

Front panel user interface

B1118 front panel

Operator controls	1 key switch STANDBY/RUN 6 dedicated rotary encoders: diode current, input offset, frequency, span, slow gain, fast gain, each with press-function 3 dedicated pushbuttons: diode on/off, slow lock, fast lock 1 menu adjust encoder 2 menu step pushbuttons
LED indicators	Four 3-colour LEDs: standby/run, laser diode, slow lock, fast lock
Display	127mm, 800x480 pixels, full colour

Connectivity

Communications	TCP/IP ethernet (10/100); USB 2.0 Type B
Laser	Standard: MOGLabs DVI-D DL socket; Option: Toptica DLPro
Power out	Photodetector supply (M8-3 Thorlabs-compatible), ± 15 V

Power and dimensions

IEC input	90 – 264 Vac @ 47 – 63 Hz
Power	28 W (laser off)
Dimensions	19" 2U, 88x422x270 mm (H x W x D), optional rack-mount ears, 3.5kg
Operating Temperature	10 - 35°C

Features

- Fully digital with high-speed FPGA signal processing.
- Bullet-proof laser operation: can reset the microcontrollers without affecting laser lock.
- Current, temperature and piezo controllers with lowest commercially available noise and drift.
- Internal spectrum analysis with high dynamic range and bandwidth.
- Complex frequency feedback locking via FPGA signal processing.
Side of fringe, top of fringe locking **included** (auto-relock in development).
- Auto-optimize of feedback servos using live noise spectral analysis.
- Signal display oscilloscope functionality on device, with specific knobs to control key functions (diode current, laser frequency and span, input signal offset, slow and fast gain).
- Completely self-contained: tune and lock to atomic resonance without computer connection.
- Full device control using on-screen menu.
- Sophisticated and intuitive GUI for remote operation via LAN or USB.
- Easy to use text-based control API; no DLL or drivers needed.
Python, LabVIEW, matlab bindings and examples provided.
- Online user manuals, software updates, app notes; no login details required.